



## HDPE FILM

### HM-9450F (EX5)- (J.P.C)

#### Product Description:

HM-9450F (EX5) is blown film grade resin which is manufactured by suspension polymerization of ethylene monomer. HM-9450F (EX5) is a bi-model high density polyethylene with 1-Butene as co monomer..

#### Characteristic Properties:

- High molar mass film grade, good stiffness and tenacity

#### Main Applications:

- For blown films with paper like quality suitable for counter bags.
- Carrier bags and wrapping films.
- Excellent processing.


#### Additives:

- Antioxidant/Process stabilizer.
- Lubricant/ acid scavenger.

#### Typical data - HM-9450F (EX5)

TEST COMPOSITION	TEST METHOD	UNIT	VALUE
Density	ISO1183	g/cm <sup>3</sup>	0.949
Fish Eye Note	Internal	note	≤3
FRR 21.6/5			29
MFR 190°/21.6	ISO1133	g/10min	8.0
MFR190°/5	ISO1133	g/10min	0.28

**Producer: Jam Petrochemical Company (J.P.C)**



**MIRA PETROKEM** Dis Tic. Ltd. Sti.

Merkez Mah. Akar Caddesi No:3 İ Tower Plaza Kat:7 No:43 Şişli/İstanbul

Tel: +90 212 2203422

Email : Info@mirapetrokem.com