

HDPE INJECTION

HD-52518 - (J.P.C)

Product Description:

52518 is a HDPE copolymer for Injection Moulding for applications requiring a good balance between easy of processability and flowability and mechanical properties.

Characteristic Properties:

- Good balance between easy of processability and flowability

Main Applications:

- Houseware.
- High fluidity.
- Injection moulding grade.

Additives:

- Thermal Antioxidant (Process Stabilizer)
- Catalyst neutralizer (acid scavenger, lubricant)

Typical data - HD-52518

RESIN PROPERTIES	TEST METHOD	UNIT	VALUE
Melt Index (190°C/ 2.16Kg)	D1238	(g/10 min)	18
Density	D1505	g/ml	0.952
THERMAL PROPERTIES	TEST METHOD	UNIT	VALUE
Vicat Softening Point	D1525	(°C)	121
MOULDED PROPERTIES	TEST METHOD	UNIT	VALUE
Flexural Modulus	D790	(MPa)	1200
Notched Izod Impact @ 23 °C	D256/A	(J/m)	19
@ on compression moulded specimen, according to ASTM D 1928°C			

Producer: Jam Petrochemical Company (J.P.C)



MIRA PETROKEM Dis Tic. Ltd. Sti.

Merkez Mah. Akar Caddesi No:3 İTower Plaza Kat:7 No:43 Şişli/İstanbul

Tel: +90 212 2203422

Email : Info@mirapetrokem.com